

SAFETY DATA SHEETS

EPOXY PRIMER PART B

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Epoxy Primer Part B
MANUFACTURER: Incredible Products LLC. ADDRESS: 1101 Lincoln Ave, Wapakoneta, OH 45895
INFORMATION PHONE: 567-297-3700 EMERGENCY PHONE: 800-424-9300

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>UNIT</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>
Benzyl Alcohol	100-51-6		N/E	N/E
Benzene 1, 3 - Dimethaneamine	1477-55-0		0.1MG/M3	0.1MG/M3
Crystalline Silica	14808-60-7		0.1MG/M3	0.1MG/M3

SECTION 2 NOTES: *Indicates toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION 3: HAZARDOUS IDENTIFICATION

Health	Flammability	Reactivity	Personal Protective Equipment
2	1	0	H

ROUTES OF EXPOSURE

INHALATION: of vapor or spray mist.

EYE or SKIN: contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE

EYES: May cause irritation but no corneal injury is likely.

SKIN: May cause irritation or allergic skin response.

INHALATION: No guide for control known, however, exposure to heated vapors can cause irritation to the nose, throat or mucous membranes.

HEALTH HAZARDS (ACUTE AND CHRONIC)

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Respiratory conditions or other allergic ailments.

CARCINOGENICITY

OSHA: NO **NTP:** NO **IARC:** NO

ADDITIONAL CARCINOGENICITY INFORMATION

No listed ingredients of this product are regulated as carcinogens.

SECTION 4: FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes. Get medical help.

SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

INHALATION: If any breathing problems occur during use. LEAVE THE AREA and get fresh air. If problems remain or occur later IMMEDIATELY get **attended** **help**.

INGESTION: Induce vomiting only if large amounts of material are ingested, and otherwise do not induce vomiting. In either case consult with a physician.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT 200F	LEL N/E	UEL N/E	METHOD USED TCC
----------------------------	-------------------	-------------------	---------------------------

EXTINGUISHING MEDIA

Use extinguishing media appropriate for surrounding fire. The product itself does not burn.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Water contamination will produce carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES

Do not enter confined area without full bunker gear including a positive pressure NIOSH approved self-contained breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Scoop up or vacuum into a container for reclamation or disposal avoid dusting.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Store in a cool dry place. Seal all partially used containers. Wash with soap and water before eating, drinking, smoking or using toilet facilities. Mixed materials contain hazards of all the components therefore, read the MSDS's of all the components prior to using material. Properly label all containers.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION

Local exhaust preferable. General exhaust acceptable, of the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA standards 1910.94, 1910.107, and 1910.108

RESPIRATORY PROTECTION

Use appropriate respirator.

PROTECTIVE GLOVES

To prevent skin contact, wear gloves, which are recommended for protection.

EYE PROTECTION

Wear safety spectacles with unperforated side shields.

OTHER PROTECTIVE EQUIPMENT

Use barrier cream on exposed skin

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating or inhaling can be harmful or fatal.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Gravity: 2.03

Boiling Point: 375F

Evaporation Rate: Slower than ether

Vapor Density: Heavier than air

Solubility in H2O: Slight

SECTION 10: STABILITY AND REACTIVITY

STABILITY- STABLE

CONDITIONS TO AVOID

Contact with open flames and all sources of ignitions and sparks.

INCOMPATIBILITY

Strong oxidants; Strong acids

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon oxides and traces of incomplete carbon compounds, silicon dioxide, metal oxides and formaldehyde.

HAZARDOUS POLYMERIZATION

Will not occur

SECTION 11: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Dispose of the material in a waste disposal site in accordance with local, state and federal law.

SECTION 12: DISCLAIMER

DISCLAIMER

The information contained herein is based on the data available and is believed to be accurate, however, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.