



TECHNICAL DATA SHEET

Easycover®

PRODUCT DESCRIPTION

Easycover® is a highly engineered cove base molding designed for the resinous flooring industry. It is easily coated, and provides numerous benefits over traditional hand troweled and existing cove moldings currently available.

STANDARD COLORS: Primer Gray

PHYSICAL PROPERTIES

4" and 6" Radius Cove Base

HEIGHT: 4" and 6"

COVE RADIUS: 1"+

BASE PORTION THICKNESS: Nominal ¼"

LENGTH: 48"

TOTAL DISTANCE OUT FROM WALL: < 1 ¼"

APPOXIMATE WEIGHT: 0.56 lbs/LF and 0.81 lbs/LF

Will Not Support Combustion

PRODUCT BENEFITS

- Superior bond to substrate when using our adhesive. • Can be used in wet environments due to our cove anchor and DoveLock™ technology.
- Physical properties mimic that of epoxy troweled cove (our competitors mimic a urethane material which is not ideal for over-coating with rigid material).
 - Will not support combustion, see web-site for video comparing competing brand.
 - Can be custom made in any length and color (minimum order of 3,000 LF)
 - Can be installed to any angle without the need or hassle of expensive pre-formed pieces.
- Color is closely matched to that of clear coated concrete to eliminate large appearance variations when applying flake or color quartz to floor and cove.

PRODUCT PERFORMANCE

ASTM TEST METHOD	DESCRIPTION	UNITS	EASYCOVER®
D790-03	Flexural Strength	Psi	270
D790-03	Flexural Modulus x 105	Psi	0.04
D790-03	Flexural Elongation	%	8
D638-03	Tensile Strength	Psi	1500
D638-03	Tensile Modulus x 105	Psi	0.15
D638-03	Tensile Elongation	%	80.21
D2583-95	Hardness, Barcol 935		0-10
D256-05	IZOD	Ft-lbs.	2.79
D695-02a	Compression Strength	Psi	7,321
D695-02a	Compression Modulus x 105	Psi	0.27
E831-06	CLTE	in/ (m.°C)	99.96
D570-98	Water Absorption		0.2521

Properties of Adhesive: Two component, 100% solids, fast drying adhesive

SURFACE PREPARATION

- Substrate should be solid, and ideally prepared to the original structural material.
- Whenever applying Easycover[®] over a previously painted surface, the bond will only be as good as the coating that Easycover[®] is adhered to.

APPLICATION

- Once substrate is prepared, apply Easycover[®] adhesive to both DoveLock bond channels and a one-half inch bead of Easycover[®] adhesive to the floor/wall corner.
 - The purpose of the bead is to create a water-proof seal between the adhesive and the Easycover[®] cove anchor.
 - Failure to have a consistent half-inch bead may allow moisture to intrude and so this step is very critical.
- Now tilt Easycover[®] up into position and apply even pressure using a soft cotton towel to make sure cove is completely pressed against the wall and floor.
 - Easycover[®] should be applied at operating temperature of that room whenever possible.
- Once Easycover[®] is removed from the box, it should be laid in a warm area, completely flat, to make sure there are no kinks or deformities. A heat gun is helpful to help the material relax. And when applying it to complex curves, this heating process will also help to accelerate the adhesive.
 - Apply the coating using brush, roll or spray.

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY

The Concrete Protector (Division of Incredible Products, LLC), warrant that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM