



TECHNICAL DATA SHEETS

SANI-TRED® EPOXY PRIMER

PRODUCT

Sani-Tred's Epoxy Primer is a two component, high solids, liquid applied, epoxy-polyamine filler surface with unique characteristics of sealing pores in concrete.

STANDARD COLORS: Gray

CURE SCHEDULE (70°)

POT LIFE (1.5 GAL Volume) 30-45 Minutes

TACK FREE (DRY TO TOUCH) N/A

RECOAT OR TOPCOAT Should be recoated within 12 hours of tack free

LIGHT FOOT TRAFFIC N/A

FULL CURE N/A

COVERAGE

Recommended for rough or porous concrete, or when outgassing is a concern.

COVERAGE PER GALLON: 1 Gal/200 Sq Ft

MIX RATIO: 1 Part Part A to 1 Part Part B

RECOMMENDED FILM THICKNESS: 7 Mils

PACKAGING INFORMATION: 2 Gallon and 10 Gallon Kits

PHYSICAL PROPERTIES

FLEXURAL STRENGTH: N/A

COMPRESSIVE STRENGTH: N/A

TENSILE STRENGTH: N/A

ADHESION: N/A

VISCOSITY: 30 (+/-5) cpois

ABRASION RESISTANCE: N/A

ULTIMATE ELONGATION: N/A

HARDNESS: Shore D= 70 (+/-5)

VOLATILE ORGANIC CONTENT: 91 grams per liter

SHELF LIFE: 1 year in unopened containers

CHEMICAL RESISTANCE

REAGENT	RATING

RATING KEY: A - NOT RECOMMENDED, B - 2 HOUR TERM SPLASH SPILL, C - 8 HOUR TERM SPLASH SPILL, D - 72 HOUR IMMERSION, E - LONG TERM IMMERSION.

NOTE: EXTENSIVE CHEMICAL RESISTANCE INFORMATION IS AVAILABLE THROUGH YOUR SALES REPRESENTATIVE.

LIMITATIONS

Not UV stable

Should be coated within 12 hours after has become tack free.

Difficult to clean up after it has cured. Do not dilute.

INSTRUCTIONS

PRODUCT MIXING: Volume mixing ratio is 1 part PART A Black Liquid to 1 part PART B White Liquid. Do not mix in an up and down motion.

SURFACE PREPARATION: Refer to the TCP Training manual and the ICRI standards for proper surface preparation.

CLEANUP: N/A

FLOOR CLEANING: N/A

RESTRICTIONS: N/A

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY

The Concrete Protector (Division of Incredible Products, LLC), warrant that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM