5 SANI-TRED

WATERPROOF CRACK RESISTANT DECORATIVE

SANI-TRED

LIQUID RUBBER WATERPROOF COATING










SANI-TRED[®] IS THE WORLD'S ONE AND ONLY LIQUID RUBBER COATING SYSTEM THAT PERMANENTLY REPAIRS AND BONDS TO CONCRETE, WOOD, FIBERGLASS, AND METAL

REPAIR, WATERPROOF AND DECORATE





BASEMENT

SANI-TRED

RUBBER COATING SYSTEMS THAT PERMANENTLY REPAIRS
AND BONDS TO CONCRETE, WOOD, FIBERGLASS, AND METAL.

PERMAFLEX, LRB, AND TAV

HAVE OVER 30 YEARS OF FIELD AND LAB TESTING, ALL SANITRED SYSTEMS GUARANTEE UNMATCHED PERFORMANCE IN ENDLESS APPLICATION ENVIRONMENTS.

- * INTERIOR AND EXTERIOR
- . 99% RADON ELIMINATION
- . CRACK PROOF SYSTEMS
- RESISTS MOISTURE VAPOR
- FLEXIBLE PENETRATION
 TECHNOLOGY
- RETAINS NEGATIVE
 HYDROSTATIC PRESSURE
- . LOW TEMP APPLICATIONS

SANI-TRED SYSTEMS S90% PERMANENT ELONGATION*

TEMPERATURE RANGE

EXCEEDS ALL ABTM VAGUUM TESTING. MAINTAINS 29" HG FOR 110 HOURS WITH ZERO LEAK

Topcoat: Apply 1 coat of PermaFlex® (240 sq ft per gal)

Patch and profile any joints, seams, cracks, holes and rough areas using LRB/TAV mixture

SANI-TRED® STEP-BY-STEP

Prepare the substrate: Make sure it is clean, dry, free of any previous applied products, foreign matter and loose or crumbling material

Prime the substrate (surface): Apply 1 cost of PermaFlex® (240 sq ft per gal)



MARINE AND BOATING APPLICATIONS



GRANIFLEX™ SYSTEM W/ POLYMER FLAKES



GRANIFLEX™ SYSTEM W/QUARTZ BROADCAST



SANI-TRED

SEE WHAT SETS SANI-TRED® APART FROM OTHER WATERPROOFING PRODUCTS.

FLEXIBLE PENETRATION[®]. PERMAFLEX[®] PENETRATES DEEPLY INTO THE PORES OF THE BUILDING MATERIALS, THEN CURES AS TOUGH AS A TRUCK TIRE THEREFORE IT IS IMPOSSIBLE FOR SANI-TRED[®] PRODUCTS TO EVER BUBBLE, PEEL OR DELAMINATE. THE FLEXIBLE PENETRATION ALLOWS PERMAFLEX[®] TO HOLD BACK EXTREME NEGATIVE HYDROSTATIC PRESSURE WITHOUT FAILURE!

ELONGATION MEMORY® TECHNOLOGY ENSURES THAT WHEN SANI-TRED® PRODUCTS ARE COMPRESSED AND RELAXED, THEY MAINTAIN THEIR ORIGINAL SHAPE AND SIZE PREVENTING DISTORTION OF THEIR ORIGINAL SHAPE AND SIZE WHICH IS A MAJOR CAUSE OF RELEASE OF COATINGS FROM POWERFUL FORCES SUCH AS FREEZE/THAW CYCLES, WATER OR GAS PRESSURE, VIBRATION AND SUDDEN SHOCK.

PERMANENT ELONGATION® SANI-TRED® PRODUCTS ARE CAPABLE OF AN AMAZING 590% ELONGATION, AND NEVER HARDEN OR BECOME BRITTLE. THEY MAINTAIN FLEXIBILITY AND BECOME STRONGER WITH AGE WITHOUT BREAKING DOWN AS OTHER COATINGS DO. SANI-TRED® PERMAFLEX® DEEPLY PENETRATES AND STRENGTHENS WEAK CONCRETE OR MORTAR JOINTS WHICH PREVENT DETACHMENT FROM THESE TYPES OF WEAK SUBSTRATES AS OTHER COATINGS ARE KNOWN TO DO.





PARKING GARAGE



POND AND FOUNTAIN WATERPROOFING



ENDLESS INDUSTRIAL APPLICATIONS

FIBERGLASS AND SWIMMING POOL REPAIR



2 PRIME SURFACE

3 FILL JOINTS AND VOIDS

TOPCOAT W/

5 OPTIONAL TOP COAT











POND AND FOUNTAIN COATING

PREPARE SURFACE

PRIME SURFACE 2



4

4 TOPCOAT W/ PERMAFLEX









GRANIFLEX™ DECORATIVE BROADCASTING SYSTEM

PREPARE SURFACE

PRIME SURFACE 2

3 BROADCAST COAT W

SEAL SURFACE









BASEMENT WATERPROOFING SYSTEM

PREPARE SURFACE

2 PRIME SURFACE

3 FILL JOINTS AND VOIDS

4 TOPCOAT W/ PERMAFLEX









ENDLESS POSSIBILITIES











WWW.SANITRED.COM



COMMERCIAL AND DISTRIBUTION SALES CALL 877-743-9732 OR 567-297-3700 WWW.THECONGRETEPROTECTOR.COM