



SCP HYDRO POLISH

PRODUCT DESCRIPTION

Scientific Concrete Polishing HYDRO POLISH was designed to repair and maintain polished concrete with its neutral PH formula, safely removing dirt without dulling your polished concrete floors. Recommended for imparting water repellency to porous construction materials such as concrete, brick, stone, concrete blocks. Low VOC meets California South Coast AQMD requirements. Fast Beading Action. Excellent Water Repellency. Water-Based Easy to Use. Dilutable, Dilution Stable. Effective at Concentration as low as 3% Actives. No SiH vented containers required.

STANDARD COLORS: Milky White

CURE SCHEDULE (70°)

TACK FREE (DRY TO TOUCH)	5 Min
RECOAT OR TOPCOAT	As soon as it's dry
LIGHT FOOT TRAFFIC	As soon as it's dry
FULL CURE	72 Hours for full repellency, 28 days full cure.

COVERAGE

COVERAGE RATE:	700-800 sq ft/ gallon
MIX RATIO:	4 Parts Water to 1 Bottle
PACKAGING INFORMATION:	1 Gallon, Quart Bottle Concentrate and 5 Gallon Concentrate, Gallon Bottle Concentrate.

PHYSICAL PROPERTIES

FLEXURAL STRENGTH: N/A **COMPRESSIVE STRENGTH:** N/A **TENSILE STRENGTH:** N/A **ADHESION:** N/A **VISCOSITY:** N/A **ABRASION RESISTANCE:** N/A
ULTIMATE ELONGATION: N/A **HARDNESS:** N/A **VOLATILE ORGANIC CONTENT:** <100 g/l **SHELF LIFE:** 12 months in unopened container
REAGENT RATING RATING KEY: A - NOT RECOMMENDED, B - 2 HOUR TERM SPLASH SPILL, C - 8 HOUR TERM SPLASH SPILL, D - 72 HOUR IMMERSION, E -
LONG TERM IMMERSION. NOTE: EXTENSIVE CHEMICAL RESISTANCE INFORMATION IS AVAILABLE THROUGH YOUR SALES REPRESENTATIVE.

LIMITATIONS

Certain types of "Cure and Seal" products may react to the sealer causing a slight discoloration (known to react with Rez Seal).

A blotchiness on the surface may occur during the first week or so during the curing phase (possible reaction to something in the concrete).

Do not install on very hot days (may produce uneven-looking areas).

Cold temps will not allow sealer to cure properly.

Good temperature range at time of application - between 50 - 95 degrees Fahrenheit: 50 degrees Fahrenheit on the low end (with no freezing that night)
and no warmer than 95 degrees Fahrenheit on the high end.

INSTRUCTIONS

PRODUCT MIXING: 1 Gallon: Empty contents of 1 Gallon concentrate in 1 Gallon pail. Add water to 1 Gallon mark. 5 Gallon: Empty contents of 5 Gallon concentrate in 5 Gallon pail. Add water to 5 Gallon mark.

SURFACE PREPARATION, POLISHED CONCRETE: After #400 Resin or Semi Metal cut, thoroughly clean floor using automatic scrubber.

SURFACE PREPARATION, MASONRY & STONE: Pressure washing is done to loosen dirt from slab. Best to use a type of "Hover Scrubber" for more even cleaning (but not absolutely necessary) and then a good rinsing with pressure wash wand to rinse off dirt.

APPLICATION: Apply by spraying Hydro Polish at 700-800 sq ft per Gallon using pump up type sprayer and finishing with Micro Fiber pad to spread evenly. Only apply at rate to maintain a wet edge across floor. Do not puddle. Remove any steaking with Micro Fiber pad while wet. Let cure 4-6 hours before continuing to #800 resin step DRY.

CLEANUP: N/A

FLOOR CLEANING: Caution! Some cleaners may affect the color of the floor installed. Test each cleaner in a small area, utilizing your cleaning technique. If no ill effects are noted, you can continue to clean with the product and process tested.

RESTRICTIONS: Restrict the use of the floor to light traffic and non-harsh chemicals until the coating is fully cured (see technical data under full cure). It is best to let the floor remain dry for the full cure cycle.

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY

Scientific Concrete Polishing (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. Scientific Concrete Polishing is NOT liable for, direct or indirect, inadvertent or consequential damages. Scientific Concrete Polishing liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if the other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM.